

# CAN

## DN 40 – 600 PN16



### Hymax® bride

Art. no	DN	Plage de serrage		CAN no 412
		Zone d'étanchéité 1 mm	Zone d'étanchéité 2 mm	
6010.040	40	<b>41-50</b>	<b>49-54</b>	
6010.050	50	<b>54-66</b>	<b>65-77</b>	745.117
6010.080	80	<b>88-99</b>	<b>98-108</b>	745.121
6010.100	100	<b>108-126</b>	<b>125-143</b>	745.122
6010.125	125	<b>130-146</b>	<b>145-162</b>	745.123
6010.150	150	<b>158-174</b>	<b>173-190</b>	745.124
6010.202	200	<b>217-233</b>	<b>232-250</b>	745.135
6010.254	250	<b>272-289</b>	<b>288-305</b>	745.136
6010.305	300	<b>315-331</b>	<b>330-347</b>	745.137
6010.353	350	<b>370-398</b>	<b>396-424</b>	
6010.404	400	<b>420-448</b>	<b>446-474</b>	745.138
6010.444	400	<b>444-472</b>	<b>470-498</b>	
6010.470	450	<b>470-498</b>	<b>496-524</b>	
6010.505	500	<b>520-548</b>	<b>546-574</b>	
6010.572	550	<b>572-600</b>	<b>598-626</b>	
6010.624	600	<b>624-652</b>	<b>650-678</b>	
6006.600	600	<b>624-652</b>	<b>650-678</b>	